

PLUG CHARGER GO 30

PLUG CHARGER GO 30

up to **30 kW**
30 min
to 100 km route



PLUG CHARGER GO

30

STANDARD 30 [kW]

CONNECTORS	CCS (4 m)	●
HOUSING	RAL Colour 9016	●
USER INTERFACE	7" Touchscreen display	●
	Emergency button	●
METERS	Output energy meter	●
COMMUNICATION	GSM (LTE) Ekoenergetyka	●
	GSM (LTE) Client	●
Order code:		DWU-A210B0000K-9016

EXTRA PAID OPTIONS

HOUSING	RAL Colour (Other)	○
	Additional branding	○
	Anti-graffiti	○
USER INTERFACE	RFID card reader	○
COMMUNICATION	Ethernet	○

● standard / available ○ option (extra paid) ✗ unavailable - absent

PLUG CHARGER GO

30

TECHNICAL SPECIFICATIONS 30 [kW]

INPUT	Power supply [V/Hz]	AC, 3 x 400 / 50
	Connection power [kVA]	33
	Connection to mains	Socket CEE 63 A 3P + N + PE
OUTPUT	Power factor	> 0,98 (for power output >25%)
	Efficiency [%]	> 94
	Maximum charging current [A]	100
COMMUNICATION	Output voltage range [V]	150 - 1000
	Charging mode	IEC 61851-1, IEC 61851-23, IEC 61851-24, ISO 15118, DIN 70121
	Protocol	OCPP 1.6-J OCPP 2.0.1
GENERAL	Housing	Aluminium
	Protection rating (excluding HMI)	IP54 / IK10
	Overall dimensions [mm] [H x W x D]	1000 x 630 x 450
	Weight [kg]	~50
	Noise [dBA]	< 60
	Operating temperature range [°C]	-25 - +55 > 40 possible output power limitation
	Operating altitude [m]	≤ 2000
	Compliance with standards	CE, LVD 2014/35/UE, EMC 2014/30UE, RED 2014/53/UE

Preliminary technical data