

TECHNICAL SPECIFICATIONS

CONFIGURATION

CCS

OUTPUT

Maximum charging current [A] 400 (up to 500)

COMMUNICATION

Charging mode IEC 61851-1
IEC 61851-23
IEC 61851-24
ISO 15118
DIN 70121

Protocol OCPP 1.6-J
OCPP 2.0.1

GENERAL

Housing Steel with galvanised coating

Protection rating IP 54
IK 10
IK8 - Touchscreen

Overall dimensions
[H x W x D] [mm] 1673 x 400 x 168

Weight [kg] ~ 150

Operating temperature range
[°C] - 25 +55
> 40 possible output power limitation

Operating altitude [m.a.s.l.] ≤ 2000

Compliance with standards CE
LVD 2014/35/UE
EMC 2014/30/UE
RED 2014/53/UE

SAT ONE +

EQUIPMENT

CONFIGURATION

CCS

CONNECTORS

DC Connectors

CCS 7 m

HOUSING

Colour RAL 9016

✓

RAL Colour (Other)

Option

Additional branding

Option

Anti-graffiti

Option

INTERFACE

Display

7" Touchscreen display with integrated RFID card reader

Emergency button

✓

Signal column

✓

COMMUNICATION

Fiber optic

✓

Catalog code

SNP
-A010G0000C
-9016