

TECHNICAL SPECIFICATIONS

CONFIGURATION

CCS

OUTPUT

Maximum charging current [A]

400 (up to 500)

COMMUNICATION

Charging mode

IEC 61851-1
IEC 61851-23
IEC 61851-24
ISO 15118
DIN 70121

Protocol

OCPP 1.6-J
OCPP 2.0.1

GENERAL

Housing

Steel with galvanised coating

Protection rating

IP 54
IK 10
IK8 - Touchscreen

Overall dimensions
[H x W x D] [mm]

1673 x 400 x 168

Weight [kg]

~ 150

Operating temperature range
[°C]

- 25 +55
for < - 20 and > + 40 possible output power limitation

Operating altitude [m.a.s.l.]

≤ 2000

Compliance with standards

CE
LVD 2014/35/UE
EMC 2014/30/UE
RED 2014/53/UE

SAT ONE +

EQUIPMENT

CONFIGURATION

CCS

CONNECTORS

DC Connectors

CCS 5 m

HOUSING

Colour RAL 9016

✓

RAL Colour (Other)

Option

Additional branding

Option

Anti-graffiti coating

Option

INTERFACE

Display

7" Touchscreen display with integrated RFID card reader

Emergency button

✓

Signal column

✓

COMMUNICATION

Fiber optic

✓

Catalog code

SNP
-A010D0000E
-9016