

# PLUG CHARGER GO

## TECHNICAL SPECIFICATIONS

MAXIMUM CHARGING POWER	30	[kW]
------------------------	----	------

### INPUT

Power supply [V / Hz]	AC, 3x400 / 50
Connection power [kVA]	33
Connection to mains	CEE 63A socket Cable connector in TNS system
Power factor	> 0,98 (for output power above 20 %)
Differential-current protection	Type A

### OUTPUT

Efficiency [%]	> 94
Maximum charging current [A]	100
Output voltage range [V]	150 - 1000

### COMMUNICATION

Charging mode	IEC 61851-1 IEC 61851-23 IEC 61851-24 ISO 15118 DIN 70121
Protocol	OCPP 1.6-J OCPP 2.0.1

### GENERAL

Housing	Aluminium
Protection rating	IP 54 IK 10 IK8 - Touchscreen
Overall dimensions [H x W x D] [mm]	1003 x 630 x 449
Weight [kg]	~ 50
Noise [dBA]	< 60
Operating temperature range [°C]	- 25 + 55 > 40 possible output power limitation
Operating altitude [m.a.s.l.]	≤ 2000
Compliance with standards	CE LVD 2014/35/UE EMC 2014/30/UE RED 2014/53/UE

# PLUG CHARGER GO

## EQUIPMENT

MAXIMUM CHARGING POWER	30	[kW]
------------------------	----	------

## CONNECTORS

DC Connectors	CCS 4 m
---------------	---------

## HOUSING

Colour	DB 703
Colour - option	RAL palette
Branding - option	Minii Midi Maxi
Anti-graffiti coating	Option

## INTERFACE

Display	7" Touchscreen display with integrated RFID card reader
output power regulation	Adjustable output power of 1 kW
Emergency button	✓

## METERS

Output energy meter	✓
---------------------	---

## COMMUNICATION

Data transfer	GSM (LTE) EEP GSM (LTE) Client Ethernet
Catalog code	PCG -S1A0-010210000 -0010D703-500001XXX0